



ABC Dry Chemical

Stored Pressure Fire Extinguishers

SUPERIOR QUALITY - MANUFACTURED AND TESTED TO ANSI/UL STANDARDS.
AMEREX IS A ISO-9002 REGISTERED FIRM.

RUGGED CONSTRUCTION - EASY AND LESS COSTLY TO MAINTAIN AND SERVICE

U/L & U.S. COAST GUARD LISTED - 6 YEAR WARRANTY

BAR CODED LABELS FOR DOCUMENTING EXTINGUISHER LOCATIONS, INSPECTIONS, MAINTENANCE AND RECHARGING

COMPLETE RANGE OF SIZES FOR ALL HAZARD REQUIREMENTS

TEMPERATURE RANGE: - 65° To + 120° F.



ABC or MULTI-PURPOSE extinguishers utilize a specially fluidized and siliconized mono ammonium phosphate dry chemical. It chemically insulates Class A fires by melting at approximately 350°F. and coats the surface to which it is applied, it smothers and breaks the chain reaction of Class B fires and will not conduct electricity back to the operator.

Available in a variety of types and sizes of Wheeled and Stationary extinguishers.

SPECIFICATIONS	ABC Dry Chemical										
	ALUMINUM					BRASS, CHROME PLATED					
VALVES											
Size & Capacity (lbs.)	2 ½	5	5	6	10 Tall	20	5	6	10 Short	10 Tall	20
Application	Nozzle	Hose and Nozzle					Hose and Nozzle				
Model Number	A417/A417T	A500/A500T	A402/A402T	A443	A456	A411	424	461	419	441	423
U/L Rating	1A: 10B:C	2A: 10B:C	3A: 40B:C	3A: 40B:C	4A: 60B:C	20A: 120B:C	2A: 10B:C	3A: 40B:C	4A: 80B:C	4A: 60B:C	20A: 120B:C
Shipping Wt. (lbs.)	5 ¼ / 5 ½	9 / 9 ¼	9 / 9 ¼	12	16 ¾	38	10 ¼	13	19 ¼	17 ¾	39
Height (in.)	14 ¾	15 ¼	15 ¼	16	20	23 ¾	15 ½	16 ¼	17 5/8	20 ½	24
Width (in.)	5 ¾	7 ¼	7 ¼	7 ¾	7 ¾	10 ¼	8	8 ½	9 ½	8 ¾	10 ¼
Depth (Diam. - in.)	3	4 ¼	4 ¼	5	5	7	4 ¼	5	6	5	7
Range (ft.)	9 - 15	12 - 18	12 - 18	15 - 21	15 - 21	15 - 21	12 - 18	15 - 21	15 - 21	15 - 21	15 - 21
Discharge Time (Sec.)	10	14	14	14 ½	20	30	14	14	22	20	30
Available with Chrome Plated Cylinder	✓	✓	✓								
F. M. Approved	✓	✓		✓	✓	✓		✓	✓	✓	✓
Standard Bracket	Wall / Vehicle-Marine			Wall			Wall				

Note: All extinguishers are U.S. Coast Guard approved with the bracket listed on the U.L. label.